

INVITATION FOR QUOTATION

DIC/UIET/2016

Package: Camera & Video Recorder

Shopping

Date: 26/09/2016

To,

Sub: Invitation for Quotations for supply of Goods

Dear Sir,

1. You are invited to submit your most competitive quotation for the following goods with item wise detailed specifications given at Annexure I,

Sr. No	Brief Description	Quantity	Delivery Period(In days)	Place of Delivery
1.	Outdoor Camera	02	30	UIET, Sector 25 Chandigarh
2.	Indoor Camera	02	30	UIET, Sector 25 Chandigarh
3.	Car Video Recorder (DASH CAM)	02	30	UIET, Sector 25 Chandigarh
4.	Network Video Recorder	01	30	UIET, Sector 25 Chandigarh

2. Quotation,

- 2.1 The contract shall be for the full quantity as described above.
- 2.2 Corrections, if any, shall be made by crossing out, initialing, dating and re writing.
- 2.3 All duties and other levies payable by the supplier under the contract shall be included in the unit price.
- 2.4 Applicable taxes shall be quoted separately for all items.
- 2.5 The prices quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
- 2.6 The Prices should be quoted in Indian Rupees only.

3. Each bidder shall submit only one quotation.
4. Quotation shall remain valid for a period not less than **55** days after the last date of quotation submission.

5. Evaluation of Quotations,

The Purchaser will evaluate and compare the quotations determined to be substantially responsive i.e. which

5.1 are properly signed ; and

5.2 confirm to the terms and conditions, and specifications.

6. The Quotations would be evaluated for all items together.

7. Award of contract:

The Purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price.

7.1 Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.

7.2 The bidder whose bid is accepted will be notified of the award of contract by the Purchaser prior to expiration of the quotation validity period. The terms of the accepted offer shall be incorporated in the purchase order.

8. Payment shall be made in Indian Rupees as follows:

Delivery and Installation - 90% of total cost

Satisfactory Acceptance - 10% of total cost

9. All supplied items are under warranty of **12** months from the date of successful acceptance of items.

10. You are requested to provide your offer latest by **17:00** hours on **13.10.2016**.

11. Detailed specifications of the items are at Annexure I.

12. Training Clause (if any) **NA**

13. Testing/Installation Clause (if any) **yes**

14. Information brochures/ Product catalogue, if any must be accompanied with the quotation clearly indicating the model quoted for.

15. Sealed quotation to be submitted/ delivered at the address mentioned below,

17. We look forward to receiving your quotation and thank you for your interest in this project.

(Authorized Signatory)

Name & Designation

Annexure-1

S.No.	Name of Equipments	Quantity	Specifications																										
1.	Outdoor Camera	02	<p>Providing installation and Fitting material, testing and commissioning Outdoor High Resolution Camera of good quality & approved make, Weather Resistant IP 66 housing, RoHS compliance etc .</p> <p>(Make: - Axis, DAHUA, SONY, BOSCH, SAMSUNG, HIKVISION, Panasonic, Godrej, Honey Well)</p> <table border="1"> <tr> <td>Image sensor</td> <td>1/3" area scan CMOS 2 megapixel</td> </tr> <tr> <td>Lens</td> <td>f=5.1 -12 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor</td> </tr> <tr> <td>Minimum illumination</td> <td>Color: 2 lux at 30 IRE, F1.8</td> </tr> <tr> <td>Shutter time</td> <td>1/10000 s to 1/2 s</td> </tr> <tr> <td>Zoom</td> <td>10x optical and 12x digital, total 120x</td> </tr> <tr> <td>Video compression</td> <td>H.264 (MPEG-4 Part 10/AVC) Motion JPEG</td> </tr> <tr> <td>Resolutions</td> <td>HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation</td> </tr> <tr> <td>Frame rate</td> <td>30/25 fps in all resolutions</td> </tr> <tr> <td>Video streaming</td> <td>Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264</td> </tr> <tr> <td>Audio compression</td> <td>AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate</td> </tr> <tr> <td>Audio Input/output</td> <td>Built-in microphone, external microphone or line input, line out</td> </tr> <tr> <td>Casing</td> <td>Camera: Metal (zinc), IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure</td> </tr> <tr> <td>Power</td> <td>Power over Ethernet (PoE) IEEE 802.3af Class 3 or</td> </tr> </table>	Image sensor	1/3" area scan CMOS 2 megapixel	Lens	f=5.1 -12 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor	Minimum illumination	Color: 2 lux at 30 IRE, F1.8	Shutter time	1/10000 s to 1/2 s	Zoom	10x optical and 12x digital, total 120x	Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG	Resolutions	HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation	Frame rate	30/25 fps in all resolutions	Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Audio Input/output	Built-in microphone, external microphone or line input, line out	Casing	Camera: Metal (zinc), IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure	Power	Power over Ethernet (PoE) IEEE 802.3af Class 3 or
Image sensor	1/3" area scan CMOS 2 megapixel																												
Lens	f=5.1 -12 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor																												
Minimum illumination	Color: 2 lux at 30 IRE, F1.8																												
Shutter time	1/10000 s to 1/2 s																												
Zoom	10x optical and 12x digital, total 120x																												
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG																												
Resolutions	HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation																												
Frame rate	30/25 fps in all resolutions																												
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264																												
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate																												
Audio Input/output	Built-in microphone, external microphone or line input, line out																												
Casing	Camera: Metal (zinc), IP66- and NEMA 4X-rated, IK10 impact-resistant aluminum enclosure																												
Power	Power over Ethernet (PoE) IEEE 802.3af Class 3 or																												

			<table border="1"> <tr> <td></td> <td>High Power over Ethernet (High PoE)</td> </tr> <tr> <td>Connectors</td> <td>RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)</td> </tr> <tr> <td>Local storage</td> <td>SD/SDHC memory card slot</td> </tr> <tr> <td>Accessories</td> <td>Mounting and connector kits wall mount bracket, sunshield, cable glands Wall bracket accessories, Pan-Tilt Motor,</td> </tr> <tr> <td>Pre/Post Alarm buffer</td> <td>Yes</td> </tr> <tr> <td>Encryption</td> <td>HTTP (SSL/TSL)</td> </tr> <tr> <td>Physical Layer</td> <td>10/100 base Tx Ethernet</td> </tr> <tr> <td>Protocol</td> <td>Minimum TCP/IP, HTTP, RTP, RTSP</td> </tr> <tr> <td>IP Support</td> <td>Static/dynamic or both</td> </tr> </table>		High Power over Ethernet (High PoE)	Connectors	RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)	Local storage	SD/SDHC memory card slot	Accessories	Mounting and connector kits wall mount bracket, sunshield, cable glands Wall bracket accessories, Pan-Tilt Motor,	Pre/Post Alarm buffer	Yes	Encryption	HTTP (SSL/TSL)	Physical Layer	10/100 base Tx Ethernet	Protocol	Minimum TCP/IP, HTTP, RTP, RTSP	IP Support	Static/dynamic or both								
	High Power over Ethernet (High PoE)																												
Connectors	RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)																												
Local storage	SD/SDHC memory card slot																												
Accessories	Mounting and connector kits wall mount bracket, sunshield, cable glands Wall bracket accessories, Pan-Tilt Motor,																												
Pre/Post Alarm buffer	Yes																												
Encryption	HTTP (SSL/TSL)																												
Physical Layer	10/100 base Tx Ethernet																												
Protocol	Minimum TCP/IP, HTTP, RTP, RTSP																												
IP Support	Static/dynamic or both																												
2.	Indoor Camera	02	<p>Supply & Installation of Indoor High Resolution Camera of good quality & approved make with 600 TVL resolution, & approved make, Weather Resistant IP 66 housing, RoHS compliance etc</p> <p>(Make: - Axis, DAHUA, SONY, BOSCH, SAMSUNG, HIKVISION, Panasonic, Godrej, Honeywell)</p> <table border="1"> <tr> <td>Image sensor</td> <td>1/3" area scan CMOS 2 megapixel</td> </tr> <tr> <td>Lens</td> <td>f= 6 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor</td> </tr> <tr> <td>Minimum illumination</td> <td>Color: 2 lux at 30 IRE, F1.8</td> </tr> <tr> <td>Shutter time</td> <td>1/10000 s to 1/2 s</td> </tr> <tr> <td>Zoom</td> <td>10x optical and 12x digital, total 120x</td> </tr> <tr> <td>Video compression</td> <td>H.264 (MPEG-4 Part 10/AVC) Motion JPEG</td> </tr> <tr> <td>Resolutions</td> <td>HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation</td> </tr> <tr> <td>Frame rate</td> <td>30/25 fps in all resolutions</td> </tr> <tr> <td>Video streaming</td> <td>Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264</td> </tr> <tr> <td>Audio compression</td> <td>AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate</td> </tr> <tr> <td>Audio Input/output</td> <td>Built-in microphone, external microphone or line input, line output</td> </tr> <tr> <td>Casing</td> <td>Camera: Metal (zinc)</td> </tr> <tr> <td>Power</td> <td>Power over Ethernet (PoE) IEEE 802.3af Class 3 or High Power over Ethernet (High PoE)</td> </tr> </table>	Image sensor	1/3" area scan CMOS 2 megapixel	Lens	f= 6 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor	Minimum illumination	Color: 2 lux at 30 IRE, F1.8	Shutter time	1/10000 s to 1/2 s	Zoom	10x optical and 12x digital, total 120x	Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG	Resolutions	HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation	Frame rate	30/25 fps in all resolutions	Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Audio Input/output	Built-in microphone, external microphone or line input, line output	Casing	Camera: Metal (zinc)	Power	Power over Ethernet (PoE) IEEE 802.3af Class 3 or High Power over Ethernet (High PoE)
Image sensor	1/3" area scan CMOS 2 megapixel																												
Lens	f= 6 mm, F1.8 - 2.1, autofocus, automatic day/night Horizontal angle of view: 50° - 5.4° M37x0.75 mounting thread for optional lens adaptor																												
Minimum illumination	Color: 2 lux at 30 IRE, F1.8																												
Shutter time	1/10000 s to 1/2 s																												
Zoom	10x optical and 12x digital, total 120x																												
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG																												
Resolutions	HDTV 1080i 1920x1080, HDTV 720p 1280x720 Standard NTSC/PAL for installation																												
Frame rate	30/25 fps in all resolutions																												
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264																												
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate																												
Audio Input/output	Built-in microphone, external microphone or line input, line output																												
Casing	Camera: Metal (zinc)																												
Power	Power over Ethernet (PoE) IEEE 802.3af Class 3 or High Power over Ethernet (High PoE)																												

				<table border="1"> <tr> <td>Connectors</td> <td>RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)</td> </tr> <tr> <td>Local storage</td> <td>SD/SDHC memory card slot</td> </tr> <tr> <td>Accessories</td> <td>Mounting and connector kits, Wall bracket accessories, Pan-Tilt Motor</td> </tr> <tr> <td>Pre/Post Alarm buffer</td> <td>Yes</td> </tr> <tr> <td>ID/Password</td> <td>Multilevel user ID/Password</td> </tr> <tr> <td>Encryption</td> <td>HTTP (SSL/TSL)</td> </tr> <tr> <td>Physical Layer</td> <td>10/100 base Tx Ethernet</td> </tr> <tr> <td>Protocol</td> <td>Minimum TCP/IP, HTTP, RTP, RTSP</td> </tr> <tr> <td>IP Support</td> <td>Static/dynamic or both</td> </tr> </table>	Connectors	RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)	Local storage	SD/SDHC memory card slot	Accessories	Mounting and connector kits, Wall bracket accessories, Pan-Tilt Motor	Pre/Post Alarm buffer	Yes	ID/Password	Multilevel user ID/Password	Encryption	HTTP (SSL/TSL)	Physical Layer	10/100 base Tx Ethernet	Protocol	Minimum TCP/IP, HTTP, RTP, RTSP	IP Support	Static/dynamic or both													
Connectors	RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power I/O terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Video out: 3x RCA Y/Pb/Pr (HD), 1x RCA Composite (SD)																																		
Local storage	SD/SDHC memory card slot																																		
Accessories	Mounting and connector kits, Wall bracket accessories, Pan-Tilt Motor																																		
Pre/Post Alarm buffer	Yes																																		
ID/Password	Multilevel user ID/Password																																		
Encryption	HTTP (SSL/TSL)																																		
Physical Layer	10/100 base Tx Ethernet																																		
Protocol	Minimum TCP/IP, HTTP, RTP, RTSP																																		
IP Support	Static/dynamic or both																																		
3.	Car Video Recorder (DASH CAM)	02	<p>Camera inside the vehicle near dashboard</p> <table border="1"> <tr> <td>Display Type and Size</td> <td>2.4" color LCD</td> </tr> <tr> <td>Image Sensor</td> <td>Low-light sensitivity CMOS, 3 mega-pixel</td> </tr> <tr> <td>Lens</td> <td>F/1.8, 130° wide angle</td> </tr> <tr> <td>G-Sensor</td> <td>3-axis</td> </tr> <tr> <td>Microphone</td> <td>Built-in</td> </tr> <tr> <td>Speaker</td> <td>Built-in</td> </tr> <tr> <td>Resolution/Frame Rate</td> <td>Full HD 1920x1080P (30fps) HD 1280x720P (30fps)</td> </tr> <tr> <td>Video Formats</td> <td>H.264 (MP4: up to 1920x1080 30fps)</td> </tr> <tr> <td>Memory Card Support</td> <td>MLC-based microSD card, 8GB/16GB/32GB/64GB (Class 10 or above)</td> </tr> <tr> <td>Connection Interface</td> <td>USB 2.0</td> </tr> <tr> <td>Network Interface</td> <td>Wi-Fi 802.11b/g/n</td> </tr> <tr> <td>Power Supply</td> <td>Input: DC 12V~24V Output: DC 5V 1A</td> </tr> <tr> <td>Battery Type</td> <td>Li-Polymer 430mAh</td> </tr> <tr> <td>Operating Temperature</td> <td>-20°C (-4°F) ~ 65°C (149°F)</td> </tr> <tr> <td>Storage Temperature</td> <td>-25°C (-13°F) ~ 70°C (158°F)</td> </tr> <tr> <td>Certification</td> <td>CE FCC RoHS KC NCC</td> </tr> </table>	Display Type and Size	2.4" color LCD	Image Sensor	Low-light sensitivity CMOS, 3 mega-pixel	Lens	F/1.8, 130° wide angle	G-Sensor	3-axis	Microphone	Built-in	Speaker	Built-in	Resolution/Frame Rate	Full HD 1920x1080P (30fps) HD 1280x720P (30fps)	Video Formats	H.264 (MP4: up to 1920x1080 30fps)	Memory Card Support	MLC-based microSD card, 8GB/16GB/32GB/64GB (Class 10 or above)	Connection Interface	USB 2.0	Network Interface	Wi-Fi 802.11b/g/n	Power Supply	Input: DC 12V~24V Output: DC 5V 1A	Battery Type	Li-Polymer 430mAh	Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)	Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)	Certification	CE FCC RoHS KC NCC
Display Type and Size	2.4" color LCD																																		
Image Sensor	Low-light sensitivity CMOS, 3 mega-pixel																																		
Lens	F/1.8, 130° wide angle																																		
G-Sensor	3-axis																																		
Microphone	Built-in																																		
Speaker	Built-in																																		
Resolution/Frame Rate	Full HD 1920x1080P (30fps) HD 1280x720P (30fps)																																		
Video Formats	H.264 (MP4: up to 1920x1080 30fps)																																		
Memory Card Support	MLC-based microSD card, 8GB/16GB/32GB/64GB (Class 10 or above)																																		
Connection Interface	USB 2.0																																		
Network Interface	Wi-Fi 802.11b/g/n																																		
Power Supply	Input: DC 12V~24V Output: DC 5V 1A																																		
Battery Type	Li-Polymer 430mAh																																		
Operating Temperature	-20°C (-4°F) ~ 65°C (149°F)																																		
Storage Temperature	-25°C (-13°F) ~ 70°C (158°F)																																		
Certification	CE FCC RoHS KC NCC																																		

					MIC, RCM
				Warranty	Two-year Limited Warranty
				Accessories	Adhesive Mount or Suction Mount (depends on your purchase selection) Car Lighter Adapter 16GB High Endurance microSDHC Memory Card
4.	Network Video Recorder	01		Recording	Real Time :8 Ch @1080p resolution i.e 25 FPS (PAL)
				Output Display	Single / Quad Screen @ 1080p / 720p / D1 resolution. With 8 Screen Display : 8 X D1 resolution
				Resolution	VGA Resolution :1024 x768,1280 x1024 ,1600 x1200.HDMI Resolution: 1280 x 720p, 1920x1080p
				Decoding	PAL: 4 x 1080p or 720p (25fps) / 8Ch @D1 (25fps), NTSC: 4x1080p or 720p (30fps) / D1 @ 25fps
				Video Decoding	Up to H.264 High Profile
				Bit Rate Control	CBR/ VBR as defined by IP Device
				Stream Input	1080p: Standard 4.5Mbps1080p (Main Stream) @30fps or D1 quality (Sub Stream) 1.5M Bit Rate
				Incoming Bandwidth	48Mbps (Main Stream 36 Mbps , Sub Stream 12Mbps)
				Outgoing Bandwidth	Max 36
				Max. Recording Stream	36Mbps, Software Alert notification on resource over allocation for added devices.Mbps (Upto 8 Channel via Web Browser)
				HDD	1 HDD each supported with 4TB
				Recording Time	1080p : Average Bit Rate 4.5 Mbps -Up to 8 Channel
				Recording Type	Continuous / Motion Based Recording
				Search Playback Mode	Time / Date / Alarm / Motion Detection
				Backup Mode	Manual Backup
				Power Switch	Power On from connected Power Source / Power Off Software control with Authentication

			Video Output	VGA & HDMI
			Audio In / Out	1 Ch Audio In / 1 Ch Audio Line Out. 2 Way Audio
			USB	2 x USB2.0 interface , support USB Keyboard for Name Input
			Web Server	Embedded server supporting Flash Video RTMP server(Multi Browser Support) 4 Live Cameras@1080p Real -Time
			Protocols	RTP / RTCP , TCP / UDP, HTTP , DHCP, DNS Client , RTMP
			Network Interface	1 RJ-45 10 /100 / 100 Mbps Network Interface Port
			POE Interface	8 RJ-45 10 / 100 Mbps POE Network Interface Port
			POE Power (Max).	120 Watt
			Input / Output	2 Way Audio
			Recording	G.711 A - Law, G.711 U - Law
			Power	Main : 110 ~ 230 VAC , Max input 180W
			Power Consumption	Max 10W(without HDD, USB, POE)
			Operating Temperature	0°C to 45°C
			Operating Humidity	0 % to 90 %
			Approvals	CE/ FCC
			Mobile App	Must be available on Android

FORMAT FOR QUOTATION SUBMISSION

(In letterhead of the supplier with seal)

Date: _____

To:

Sl. No.	Description of goods (with full Specifications)	Qty.	Unit	Quoted Unit rate in Rs. (Including Ex Factory price, excise duty, packing and forwarding, transportation, insurance, other local costs incidental to delivery and warranty/ guaranty commitments)	Total Price (A)	Sales tax and other taxes payable	
						In %	In figures (B)
Total Cost							

Gross Total Cost (A+B): Rs. _____

We agree to supply the above goods in accordance with the technical specifications for a total contract price of Rs. _____ (Amount in figures) (Rupees _____ amount in words) within the period specified in the Invitation for Quotations.

We confirm that the normal commercial warranty/ guarantee of ———— months shall apply to the offered items and we also confirm to agree with terms and conditions as mentioned in the Invitation Letter.

We hereby certify that we have taken steps to ensure that no person acting for us or on our behalf will engage in bribery.

Signature of Supplier

Name: _____

Address: _____

Contact No: _____