

INVITATION FOR QUOTATION

DIC/UIET/2016

Package: Blade Chassis and Blade Server

Shopping

Date: 15/11/2016

To,

Sub: Invitation for Quotations for supply of Goods

Dear Sir,

1. You are invited to submit your most competitive quotation for the following goods with item wise detailed specifications given at Annexure I,

Sr. No	Brief Description	Quantity	Delivery Period(In days)	Place of Delivery
1.	Blade Chassis	01	30	UIET, Sector 25 Chandigarh
2.	Blade Server	02	30	UIET, Sector 25 Chandigarh

2. Quotation,
 - 2.1 The contract shall be for the full quantity as described above.
 - 2.2 Corrections, if any, shall be made by crossing out, initialing, dating and re writing.
 - 2.3 All duties and other levies payable by the supplier under the contract shall be included in the unit price.
 - 2.4 Applicable taxes shall be quoted separately for all items.
 - 2.5 The prices quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
 - 2.6 The Prices should be quoted in Indian Rupees only.
3. Each bidder shall submit only one quotation.
4. Quotation shall remain valid for a period not less than **55** days after the last date of quotation submission.
5. Evaluation of Quotations,

The Purchaser will evaluate and compare the quotations determined to be substantially responsive i.e. which

5.1 are properly signed ; and

5.2 confirm to the terms and conditions, and specifications.

6. The Quotations would be evaluated for all items together.

7. Award of contract:

The Purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price.

7.1 Notwithstanding the above, the Purchaser reserves the right to accept or reject any quotations and to cancel the bidding process and reject all quotations at any time prior to the award of contract.

7.2 The bidder whose bid is accepted will be notified of the award of contract by the Purchaser prior to expiration of the quotation validity period. The terms of the accepted offer shall be incorporated in the purchase order.

8. Payment shall be made in Indian Rupees as follows:

Delivery and Installation - 90% of total cost

Satisfactory Acceptance - 10% of total cost

9. All supplied items are under warranty of **12** months from the date of successful acceptance of items.

10. You are requested to provide your offer latest by **17:00** hours on **29.11.2016**.

11. Detailed specifications of the items are at Annexure I.

12. Training Clause (if any) **NA**

13. Testing/Installation Clause (if any) **yes**

14. Information brochures/ Product catalogue, if any must be accompanied with the quotation clearly indicating the model quoted for.

15. Sealed quotation to be submitted/ delivered at the address mentioned below,

University Institute of Engineering and Technology, Sector-25, South Campus Panjab University Chandigarh.

17. We look forward to receiving your quotation and thank you for your interest in this project.

(Authorized Signatory)

Name & Designation

Annexure-1

S.No.	Name of Equipments	Quantity	Specifications																				
1.	Blade Chassis	01	<p>s</p> <table border="1"> <tr> <td data-bbox="657 583 885 625">Blade Chassis:</td> <td data-bbox="885 583 1528 625" style="text-align: right;">1 no.</td> </tr> <tr> <td data-bbox="657 625 885 768">Chassis attributes</td> <td data-bbox="885 625 1528 768">Rack Mount Modular Blade Chassis capable of providing 0.5 - 0.7 U of density for 2 Socket Server. Chassis should support dual socket as well as four socket server.</td> </tr> <tr> <td data-bbox="657 768 885 810">I/O slots</td> <td data-bbox="885 768 1528 810">Up to 8 x PCIe 3.0 I/O expansion slots</td> </tr> <tr> <td data-bbox="657 810 885 873">Redundancy</td> <td data-bbox="885 810 1528 873">Should support Hot Pluggable & Redundant Management and I/O Modules</td> </tr> <tr> <td data-bbox="657 873 885 1031">Ethernet Module</td> <td data-bbox="885 873 1528 1031">2 Hot plug Redundant Ethernet Switch with 1Gigabit Ethernet Ports with L3 / L2 modules for external connectivity. The connection to the server blades should be through internal fabric of 1G</td> </tr> <tr> <td data-bbox="657 1031 885 1352">Management</td> <td data-bbox="885 1031 1528 1352"> <ul style="list-style-type: none"> • Management Controller shall manage all resources (server nodes and shared infrastructure) in a single web console • Common Management console from Server OEM should support local and remote management, consistent with other products from the same OEM • Server nodes must contain proven Management processor and Remote Management controller for agent-free, automated systems management </td> </tr> <tr> <td data-bbox="657 1352 885 1419">Cooling</td> <td data-bbox="885 1352 1528 1419">Redundant hot-swappable fans to provide cooling to the I/O components in the system</td> </tr> <tr> <td data-bbox="657 1419 885 1530">Power Supplies</td> <td data-bbox="885 1419 1528 1530">Hot-plug Power Supply Units in N+N redundant configuration as per fully loaded chassis power requirement calculation.</td> </tr> <tr> <td data-bbox="657 1530 885 1640">Blade Server support</td> <td data-bbox="885 1530 1528 1640">The chassis should support intermixing of both Intel Xeon processor based 2-socket, 4 socket servers, as well as storage blade</td> </tr> <tr> <td data-bbox="657 1640 885 1682">Warranty</td> <td data-bbox="885 1640 1528 1682">3 years 24*4 Onsite Warranty by OEM</td> </tr> </table>	Blade Chassis:	1 no.	Chassis attributes	Rack Mount Modular Blade Chassis capable of providing 0.5 - 0.7 U of density for 2 Socket Server. Chassis should support dual socket as well as four socket server.	I/O slots	Up to 8 x PCIe 3.0 I/O expansion slots	Redundancy	Should support Hot Pluggable & Redundant Management and I/O Modules	Ethernet Module	2 Hot plug Redundant Ethernet Switch with 1Gigabit Ethernet Ports with L3 / L2 modules for external connectivity. The connection to the server blades should be through internal fabric of 1G	Management	<ul style="list-style-type: none"> • Management Controller shall manage all resources (server nodes and shared infrastructure) in a single web console • Common Management console from Server OEM should support local and remote management, consistent with other products from the same OEM • Server nodes must contain proven Management processor and Remote Management controller for agent-free, automated systems management 	Cooling	Redundant hot-swappable fans to provide cooling to the I/O components in the system	Power Supplies	Hot-plug Power Supply Units in N+N redundant configuration as per fully loaded chassis power requirement calculation.	Blade Server support	The chassis should support intermixing of both Intel Xeon processor based 2-socket, 4 socket servers, as well as storage blade	Warranty	3 years 24*4 Onsite Warranty by OEM
Blade Chassis:	1 no.																						
Chassis attributes	Rack Mount Modular Blade Chassis capable of providing 0.5 - 0.7 U of density for 2 Socket Server. Chassis should support dual socket as well as four socket server.																						
I/O slots	Up to 8 x PCIe 3.0 I/O expansion slots																						
Redundancy	Should support Hot Pluggable & Redundant Management and I/O Modules																						
Ethernet Module	2 Hot plug Redundant Ethernet Switch with 1Gigabit Ethernet Ports with L3 / L2 modules for external connectivity. The connection to the server blades should be through internal fabric of 1G																						
Management	<ul style="list-style-type: none"> • Management Controller shall manage all resources (server nodes and shared infrastructure) in a single web console • Common Management console from Server OEM should support local and remote management, consistent with other products from the same OEM • Server nodes must contain proven Management processor and Remote Management controller for agent-free, automated systems management 																						
Cooling	Redundant hot-swappable fans to provide cooling to the I/O components in the system																						
Power Supplies	Hot-plug Power Supply Units in N+N redundant configuration as per fully loaded chassis power requirement calculation.																						
Blade Server support	The chassis should support intermixing of both Intel Xeon processor based 2-socket, 4 socket servers, as well as storage blade																						
Warranty	3 years 24*4 Onsite Warranty by OEM																						
2.	Blade Server	02	<table border="1"> <tr> <td data-bbox="657 1969 885 2009">Server</td> <td data-bbox="885 1969 1528 2009" style="text-align: right;">2 nos.</td> </tr> </table>	Server	2 nos.																		
Server	2 nos.																						

			<table border="1"> <tr> <td>Processor</td> <td>2 x Intel E5-2630v4 10-Core latest generation of at least 2.2 GHz/higher with at least 25MB/higher Cache and 9.6 GT/s QPI</td> </tr> <tr> <td>Chipset</td> <td>Latest OEM chipset supporting an optimized for the above processor</td> </tr> <tr> <td>Form Factor</td> <td>Blade</td> </tr> <tr> <td>Memory</td> <td>RAM (min/max): 64 GB DDR-4 ECC RDIMM min. 2400 Mhz RAM upgradable to 768GB</td> </tr> <tr> <td>Flash/SD/SSD Drive</td> <td>Server should be configured with min. 16GB Flash/SSD/SD or higher in redundant configuration for booting Hypervisor/OS.</td> </tr> <tr> <td>Hard Disk drives</td> <td>2 x 1.2 TB Hot Swap 12 Gb/s 10K RPM SAS Hard Disk Drives configured in RAID 1</td> </tr> <tr> <td>I/O slots</td> <td>Access to 2 x PCIe 3.0 (x8) expansion slots</td> </tr> <tr> <td>Graphics</td> <td>Integrated Graphics with at least 16MB Video Memory</td> </tr> <tr> <td>Network</td> <td>Integrated Dual port 10G Adapter</td> </tr> <tr> <td>Host Bus Adaptor</td> <td>Blade Server should have provision for connectivity to external SAN Storage on 8 Gbps.</td> </tr> <tr> <td>Server Management</td> <td>OEM embedded controller with IPMI 2.0 compliance and Server Management Tool from same OEM</td> </tr> <tr> <td rowspan="2">Industry standard certifications & benchmarks</td> <td>The quoted server models should have the following Certifications: Microsoft® Windows Server® 2008 R2 SP1, (includes Hyper-V®), Microsoft Windows Server 2012, Microsoft Windows Server 2012 R2 (includes Hyper-V), Novell® SUSE® Linux Enterprise Server, Red Hat® Enterprise Linux®. FCC, UL, ROHS</td> </tr> <tr> <td>The quoted server model must have published benchmark on spec.org/tpc.org</td> </tr> <tr> <td>Security</td> <td>Security Power-on password Administrator's password Keyboard password Out of band remote management Chipset with: SSL encryption Secure Shell</td> </tr> <tr> <td>Warranty</td> <td>3 years 24*7 Onsite Warranty by OEM</td> </tr> </table>	Processor	2 x Intel E5-2630v4 10-Core latest generation of at least 2.2 GHz/higher with at least 25MB/higher Cache and 9.6 GT/s QPI	Chipset	Latest OEM chipset supporting an optimized for the above processor	Form Factor	Blade	Memory	RAM (min/max): 64 GB DDR-4 ECC RDIMM min. 2400 Mhz RAM upgradable to 768GB	Flash/SD/SSD Drive	Server should be configured with min. 16GB Flash/SSD/SD or higher in redundant configuration for booting Hypervisor/OS.	Hard Disk drives	2 x 1.2 TB Hot Swap 12 Gb/s 10K RPM SAS Hard Disk Drives configured in RAID 1	I/O slots	Access to 2 x PCIe 3.0 (x8) expansion slots	Graphics	Integrated Graphics with at least 16MB Video Memory	Network	Integrated Dual port 10G Adapter	Host Bus Adaptor	Blade Server should have provision for connectivity to external SAN Storage on 8 Gbps.	Server Management	OEM embedded controller with IPMI 2.0 compliance and Server Management Tool from same OEM	Industry standard certifications & benchmarks	The quoted server models should have the following Certifications: Microsoft® Windows Server® 2008 R2 SP1, (includes Hyper-V®), Microsoft Windows Server 2012, Microsoft Windows Server 2012 R2 (includes Hyper-V), Novell® SUSE® Linux Enterprise Server, Red Hat® Enterprise Linux®. FCC, UL, ROHS	The quoted server model must have published benchmark on spec.org/tpc.org	Security	Security Power-on password Administrator's password Keyboard password Out of band remote management Chipset with: SSL encryption Secure Shell	Warranty	3 years 24*7 Onsite Warranty by OEM
Processor	2 x Intel E5-2630v4 10-Core latest generation of at least 2.2 GHz/higher with at least 25MB/higher Cache and 9.6 GT/s QPI																															
Chipset	Latest OEM chipset supporting an optimized for the above processor																															
Form Factor	Blade																															
Memory	RAM (min/max): 64 GB DDR-4 ECC RDIMM min. 2400 Mhz RAM upgradable to 768GB																															
Flash/SD/SSD Drive	Server should be configured with min. 16GB Flash/SSD/SD or higher in redundant configuration for booting Hypervisor/OS.																															
Hard Disk drives	2 x 1.2 TB Hot Swap 12 Gb/s 10K RPM SAS Hard Disk Drives configured in RAID 1																															
I/O slots	Access to 2 x PCIe 3.0 (x8) expansion slots																															
Graphics	Integrated Graphics with at least 16MB Video Memory																															
Network	Integrated Dual port 10G Adapter																															
Host Bus Adaptor	Blade Server should have provision for connectivity to external SAN Storage on 8 Gbps.																															
Server Management	OEM embedded controller with IPMI 2.0 compliance and Server Management Tool from same OEM																															
Industry standard certifications & benchmarks	The quoted server models should have the following Certifications: Microsoft® Windows Server® 2008 R2 SP1, (includes Hyper-V®), Microsoft Windows Server 2012, Microsoft Windows Server 2012 R2 (includes Hyper-V), Novell® SUSE® Linux Enterprise Server, Red Hat® Enterprise Linux®. FCC, UL, ROHS																															
	The quoted server model must have published benchmark on spec.org/tpc.org																															
Security	Security Power-on password Administrator's password Keyboard password Out of band remote management Chipset with: SSL encryption Secure Shell																															
Warranty	3 years 24*7 Onsite Warranty by OEM																															

FORMAT FOR QUOTATION SUBMISSION

(In letterhead of the supplier with seal)

Date: _____

To:

Sl. No.	Description of goods (with full Specifications)	Qty.	Unit	Quoted Unit rate in Rs. (Including Ex Factory price, excise duty, packing and forwarding, transportation, insurance, other local costs incidental to delivery and warranty/ guaranty commitments)	Total Price (A)	Sales tax and other taxes payable	
						In %	In figures (B)
Total Cost							

Gross Total Cost (A+B): Rs. _____

We agree to supply the above goods in accordance with the technical specifications for a total contract price of Rs. _____ (Amount in figures) (Rupees _____ amount in words) within the period specified in the Invitation for Quotations.

We confirm that the normal commercial warranty/ guarantee of ———— months shall apply to the offered items and we also confirm to agree with terms and conditions as mentioned in the Invitation Letter.

We hereby certify that we have taken steps to ensure that no person acting for us or on our behalf will engage in bribery.

Signature of Supplier

Name: _____

Address: _____

Contact No: _____