

2054

B.E. (Biotechnology) Eighth Semester  
BIO-814: Modeling and Simulation of Bioprocesses

Time allowed: 3 Hours

Max. Marks: 50


**NOTE:** Attempt five questions in all, including Question No. 1 which is compulsory and selecting two questions from each Section. State clearly your assumptions.

x-x-x

- 1) Write briefly: (2×5 = 10)
- What is product yield with respect to substrate?
  - Write down unsteady state mass balance for dynamic model of (CSTR)?
  - Define metabolic engineering and what are the significance of metabolic Engineering?
  - Define useful measurable parameter is the respiratory quotient (RQ) with suitable example?
  - Write down advantage and disadvantage of fed batch reactor.



SECTION-A

2. A) An electric heating-coil is immersed tank. Solvent at 15°C with heat capacity 2.1 kJ kg<sup>-1</sup>°C is fed into the tank at of 15 kg h<sup>-1</sup>. Heated solvent is discharged at the same flow rate. The tank is filled initially with 125 kg cold solvent at 10°C. The rate of heating by electric coil is 800 W. Calculate the time required for the temperature of solvent to reach 60°C.
- B) The simple first order conversion of an enzyme *A* into product *B* may be complicated by the conversion *B* into new product *C*. This can be describing by the equation:



Each step of the reaction will have a unique rate constant  $K_1$  for the conversion of an enzyme *A* into *B* and  $K_2$  for the conversion of *B* to *C*. if the initial concentration of *A* at time  $A_0$ . Derive the concentration of *A*, *B*, and *C* in terms of time and rate constant. Also plot the concentration profile of reactant with time. (4, 6)

3. A) Assume that the cell can convert 67% of carbon source to biomass. Hexadecane and glucose are used as carbon sources. Calculate the stoichiometric coefficients of following reactions:



- B) Water enters a tank at the rate of 25 L/min. it is being withdrawn at the rate which varies according to  $25(1 - e^{-0.1t})$  L/min., where *t* is minutes. If the tank initially contains 50 L. How many gallons (liter) of water will the tank contains when the steady state is reached? (7, 3)
4. A) Aspartase enzyme is used in batch reaction for manufacture of aspartic acid, a component of low calorie sweetener. In the substrate range of interest the conversion can describe using michalis- menten kinetics with 4.0 g l<sup>-1</sup>. The substrate solution contains 1.5 g l<sup>-1</sup> ammonium fumarate, the reaction stop when 85% of substrate is converted. At 32°C,  $V_{max}$  for enzyme 5.9 g l<sup>-1</sup> h<sup>-1</sup> and its half life is 10.5 d. At 37°C  $V_{max}$  increases to 8.5 g l<sup>-1</sup> h<sup>-1</sup> but the half life is reduced to 2.3 d. Which operating temperature would you recommended?
- B) A tank contains 1000 liters of pure water. Brine that contains 0.05 kg of salt per liter of water enters the tank at a rate of 5 liters/min. Brine that contains 0.04 kg of salt per liter of water enters the tank at the rate of 10 liters/min. The solution is kept thoroughly mixed and drains from the tank at 15 liters/min. How much salt is left in the tank after 1 hour? (5, 5)

P.T.O.

(2)

**SECTION-B**

5. A) In fed-batch fermentor, substrate stream is added continuously to the reactor. Develop a suitable mathematical model with the following kinetics:

$$r_x = \mu X, \quad \mu = \frac{\mu_{\max} S}{K_s + S}, \quad r_s = -\frac{r_x}{Y}, \quad D = \frac{F_0}{V}$$

Convert the model in the dimensionless using the following transformation:

$$V' = \frac{V}{V_0}, \quad X' = \frac{X}{YS_0}, \quad S' = \frac{S}{S_0}, \quad F' = \frac{F_0}{V_0 \mu}, \quad K'_s = \frac{K_s}{S_0}, \quad \mu' = \frac{\mu}{\mu_m}, \quad F' = \frac{dV'}{dt'} \quad \text{and} \quad t' = t\mu_m$$


- B) Inversion of sucrose by Invertase follows substrate inhibition kinetics. The following data is given:

$$S_0 = 100 \text{ m mol l}^{-1}, \quad S_{\max} = 20 \text{ m mol l}^{-1}, \quad K_m = 8 \text{ m mol l}^{-1}, \quad V_{\max} = 4.45 \text{ m mol min}^{-1} \text{ l}^{-1}$$

Calculate productivity for CSTR to get the maximum product?

(6, 4)

6. A) Enzymatic isomerization glucose to fructose can be expressed by reaction mechanism:



The kinetic parameter is:

$$\frac{V_{m,s}}{K_{m,s}} = 0.128, \quad \frac{V_{m,p}}{K_p} = 0.098, \quad \frac{1}{K_{m,s}} = 0.383, \quad \frac{1}{K_p} = 0.25$$

If the feed (glucose) concentration is 1.0 kg mole/liter and desired conversion is 40%. Compare the productivity in above rate expression in CSTR & FPR.

- B) Fermentation by *Candida utilis* exhibits substrate inhibition kinetics in the form:

$$\mu = \frac{\mu_{\max} \cdot S}{K_s + S + S^2/K_i}$$

Where  $S$  is the substrate,  $\mu$  is the specific growth rate and  $\mu_{\max}$  is the maximum specific growth rate. For continuous fermentation using sterile feed, derive equation for the steady state variation of the biomass concentration ( $X$ ), Substrate concentration ( $S$ ) and their maximum productivity ( $DX$ ). (5, 5)

7. A) Discuss the Monod chemostat model with recycle system.

- B) An arrangement consists of two stirred tanks reactor connected in series. The first reactor has an operational volume of 75 liters and the second reactor having an operational volume of 25 liters. A sterile feed is given to the first reactor containing 3.5 g/liter of substrate and fed at the rate of 15 liters/hr. Using Monod's kinetic model to describe the growth kinetics, it is found that the value of  $K_s$  is 0.11 g/liter,  $Y_{x/s}$  is 0.4 and maximum specific growth rate is  $0.22 \text{ hr}^{-1}$ . Determine the steady state concentration of substrate in the second reactor. (4, 6)